

# CTV SoniXs

REVOLUTIONIZE YOUR  
END-OF-LINE [PACKAGING]  
PERFORMANCE



All-Electric Compression Unitizer



Up To 5 SoniXs® Narrow Sealing Heads




Up To 220 Loads Per Hour



Machine Options Available

**EAM—MOSCA®**



# CTV SoniXs

## 5 HEADED ELECTRIC COMPRESSION UNITIZER

The CTV SoniXs® all-electric compression unitizer features up to five narrow SoniXs® strapping heads. This allows for single platen hits on the widest variety of load sizes in the industry for maximum strap placement flexibility and increased throughput. The CTV SoniXs® also comes with Dual Pawl Platen Support.

Optional "MoscaTrak" diagnostics and data collection screen provides real-time data to determine corrective actions and maximize up-time.



## The Ultimate Strap Sealing Solution

Mosca's proprietary SoniXs® ultrasonic sealing heads have revolutionized strapping systems offering significant and proven advantages over traditional heat-seal technologies, including cost, maintenance, and longevity across all industries and applications.

Unlike heat seal systems, SoniXs® strap seals are made without the use of high-temperature components, reducing energy costs, improving safety, and generating lower emissions.

A SoniXs® seal is harder to break, and the visible evidence of a break is irreversible. The distinctive impression on Mosca's ultrasonically-sealed strap makes it easy to identify if the packaging has been tampered with. The seal will be distinguishably different if a strap is removed and reapplied.

---

## Key Benefits

- + **INCREASED SEAL STRENGTH**
  - + **COST SAVINGS**
  - + **LASTING DURABILITY**
  - + **CONSISTENT SEALING**
  - + **WORRY-FREE PRODUCT SECUREMENT**
  - + **ENERGY CONSERVATION**
  - + **LOW MAINTENANCE**
  - + **SEALS BOTH PP AND PET**
-

---

## TECHNICAL SPECIFICATIONS

---

### Production Rate

2 x 0 Pattern - Without Lances: 220 With Lances: 170  
2 x 2 Pattern - Without Lances: 105 With Lances: 90

---

### No. of Strapping Heads

Model 803: 3 Heads  
Model 804: 4 Heads  
Model 805: 5 Heads

---

### Head Spacing

9" - 9" - 23.5" - 15" (229mm - 229mm - 597mm - 381mm)

---

### Electrical

480VAC 3pH, 60 Hz, 40 Amps

---

### Controls

O.E.M. Controls: Allen-Bradley CompactLogix PAC Standard

---

### Conveyor

Dual strand tangential chain drive for consistent load positioning. Heavy duty 2.5" (64mm) diameter steel rollers on 3.5" (89mm) and 4" (102mm) centers.

---

### Conveyor Speed

Standard: 60 Ft Per Minute  
Optional: 45 Ft Per Minute

---

### Compression

Electric Compression.  
Touch up to 8000 Lbs. 10 settings.

---

### Load Dimensions

Width: 20" - 98" (508mm - 2489mm) Min Length: 20" (508mm)  
Height Without Lances: 8" - 96" (203mm - 2439mm)  
Height With Lances: 12" - 96" (305mm - 2439mm)  
Max Diagonal: 100" (2540mm) (Applies only to the optional internal turntable)

---

### Strapping

PET strap: 9mm, 11mm, or 12mm  
PP strap: 12mm

---

### Strap Seal

SoniXs® ultrasonic seal

---

## OPTIONS

---

- + Moscatrak (performance and maintenance diagnostic tool)
- + Internal turntable (cross-arm style. Continuous in either direction. Load capacity 2,500 lbs)
- + Lances (PVFA) feed strap through pallet voids with "Clear path" sensing
- + Spare head/test stand
- + Manual control station
- + Extra high platen opening
- + End of coil strap catching and strap splicing device
- + Custom paint (RAL color chart)
- + Wide body

SCAN  
HERE




Want to see the  
CTV SoniXs®  
in action? Use  
the QR code  
to learn more.

---

## MACHINE DIMENSIONS

---



---

CONTACT US FOR A FREE CONSULTATION TODAY  
[www.eammosca.com](http://www.eammosca.com) | [info@eammosca.com](mailto:info@eammosca.com)

### U.S.A., Latin America & The Caribbean

#### EAM-Mosca Corporation

675 Jaycee Drive, Hazle Township, PA 18202  
Phone: 800.456.3420 / 570.459.3426  
Fax: 570.455.2442

### Canada

#### EAM-Mosca Canada Ltd.

170 William Smith Drive, Whitby, Ontario, L1N 9N3  
Phone: 800.633.6392 / 905.665.8225  
Fax: 905.665.8188