Saturn S4

Automatic rotary ring stretch wrapper





we dare to try anything

Saturn S4



ystem

- +MAXIMUM CAPACITY: up to 70 pallets/hour
- Maximum quality, high performance and minimum maintenance
- It is the best alternative to the turntable wrapping machine: more balanced, with less mechanical wear and maintenance. The load remains static: the film reels rotate around the load
- + Guaranteed savings of stretch film: 300% film pre-stretching. 1 m of film becomes 4 m
- + Finishing without tails of film thanks to our efficient cut and welding device
- + Electronic and self-adjusting tension control depending on the profile of the load
- *Possibility of applying efficient dustproof and rainproff wrappings
- +Possibility of wrapping at ground level
- +Capable of applying bands (strips) at any height of the load

111 N. Orange Ave. Suite 800 • FL 32801 Orlando (USA) Tel. +1 470 846 9736 • E-mail: sales@movitec-ws.com

Technical properties

- + Voltage: 480 V 3P / 60Hz +PE
- + Power supply: 4,5 kW
- + Compressed air: 6 bar
- + Air consumption: 8 I/cicle
- + Air consumption with top film: 64 l/cicle

STRETCH WRAPPING FILM:

- + Maximum width: 20"
- + Maximum diameter: 9,8"
- + Core diameter: 3"
- + Film thickness: up to 140 (gauge)

D17

D20

LOAD DIMENSIONS:

Maximum width Maximum diagonal	43 68	51 80				1
Maximum height Possibility to ad	*With conveyo	82* ors height 19".	200	Roping device	EPS: Electronic Pre-	stretch Syst
	for loads h	igher than 82".				
	¥-c					
		la.	The state of the s	Quick-Load	ACBA: Automa Board Appl	atic Corner lication
		CI .			D17	D20
			RODUCTION	Maximum capacity (pall	ets/hour) 70	67
н		M	ACHINERY DIMENSIO	NS A (inches) B (inches)		276 79
1- 11		Α		C (inches)		118
В		С	D	D (inches)		79
	T			E (inches)	142	150
	,			F (inches)	4	165
	63	- 4	Э	G (inches)		102
	1			H (inches)	90	98
17	~ ///			T		
	a la		N Hotelstone			
<u> </u>			<u> </u>			
	92		9	0000	www.movite	c-ws.com

Add-ons

and Rain-proof