Saturn S6

Automatic rotary ring stretch wrapper





we dare to try anything




Reliable & efficient wrapping machines

- + HIGH CAPACITY: up to 120 pallets/hour
- + Maximum quality, high performance and minimum maintenance
- + It is the most versatile: it can evolve to a Saturn S8 model to get higher capacities
- + The load remains static: the film reels rotate around the load
- + Guaranteed savings of stretch film: 300% film pre-stretching
- + 1 m of film becomes 4 m
- + Finishing without tails of film thanks to our efficient cut and welding device
- + Electronic and self-adjusting tension control depending on the profile of the load
- + Possibility of applying efficient dustproof and rainproff wrappings
- + Possibility of wrapping at ground level
- + Capable of applying bands (strips) at any height of the load

Add-ons




















Saturn S6



		D17	D20	D23	D26	D29
PRODUCTION	Maximum capacity (p/h)	120	110	90	85	75
MACHINERY DIMENSIONS	A (inches)		276		394	
	B (inches)		79		118	
	C (inches)		18		158	
	D (inches)		79		118	
	E (inches)	142	150	177		193
	F (inches)			165*		
	G (inches)			102*		
	H (inches)	90	98	124		136
LOAD DIMENSIONS	Maximum width (inches)	42	50	58		70
	Maximum diagonal (inches)	68	80	92	104	116
	Maximum height (inches)	82 (conveyors height 19") *				
POWER SUPPLY	Voltage	400 V 3P + N + PE 60 Hz				
	Compressed air pressure (bar)	6				
STRETCH FILM	Maximum height (inches)		2	0		
	Maximum diameter (inches)	9,8				
	Inner core diameter (inches)		;	3		
	Film thickness (gauge)	up to 140				
TOP FILM	Maximum height (inches)	62	70	78		78
	Maximum diameter (inches)		1	1		·
	Inner core diameter (inches)		_ :	3		
	Film thickness (gauge)		12	20		

^{*} Possibility to adapt the frame of the machine for loads higher than 82"

